DUO 2



Combination of oil-free two-cylinder compressor and two suction units (dry suction) in a stylish Ekom cabinet. Source of clean compressed air and vacuum (suction) for two* dental units. Its compact design is space-saving and the soundproofing cabinet allows placement directly inside the treatment room.

DUO 2 - with noise reduction cabinet

DUO 2/M - with noise reduction cabinet, with dryer

Without dryer

	DUO 2
Dryer	✘
Noise reduction cabinet	✔
Suction unit	✔
Number of dental units	2
Nominal voltage / frequency	230 V / 50 Hz 230 V / 60 Hz
Motor performance	1.1 kW
Air tank capacity	25 l
Compressor efficiency (working pressure 6 - 8 bar)	135 $l.min^{-1}$ / 6 bar
Duty cycle	S1 - 100 %
Max. output capacity	2x1100 $l.min^{-1}$
Max. vacuum	12 kPa
Noise level	≤ 51,5 dB (A)
Weight	133 kg
Dimensions	560 x 685 x 1255 mm

EKOM spol. s r.o., Priemyselná 5031/18, 921 01 Piešťany, Slovak Republic
T +421 33 7967 211, F +421 33 7967 223, info@ekom.sk, www.ekom.sk

https://stomdevice.ru - стоматологическое и зуботехническое оборудование с доставкой по России и СНГ

With membrane dryer

	DUO 2/M
Dryer	✔(MD)
Noise reduction cabinet	✔
Suction unit	✔
Number of dental units	2
Nominal voltage / frequency	230 V / 50 Hz 230 V / 60 Hz
Motor performance	1.1 kW
Air tank capacity	25 l
Compressor efficiency (working pressure 6 - 8 bar)	104 $l.min^{-1}$ / 6 bar
Duty cycle	S1 - 100 %
Degree of air drying (pressure dew point PDP)	+3 °C at 7 bar
Max. output capacity	2x1100 $l.min^{-1}$
Max. vacuum	12 kPa
Noise level	≤ 55 dB (A)
Weight	138 kg
Dimensions	560 x 685 x 1255 mm

- Data on weight and dimension are for informational purposes only
- Technical modifications are subject to change

Diagrams



