stomdevice

R-ONE
TECHNICAL DATASHEET



https://stomdevice.ru - стоматологическое и зуботехническое оборудование с доставкой по России и СНГ

Holder Types



Premill Holder



Glass Ceramic Holder



Multiple Glass Ceramic Holder

Applications



Prefab Abutments



Crown Bridge



Inlay, Onlay and Veners

Screw Retantion Bridge

Denture - Type 1

Denture - Type 2

Surgical Guide

Model Casting

Model

Splint

Material Types

Glass - Ceramic	Premill	PMMA	Composite	Titanium	Zirconia
CoCr	Alumina	Wax	Fiber	Peek	

https://stomdevice.ru - стоматологическое и зуботехническое оборудование с доставкой по России и СНГ

Technical Specifications **R-ONE**

AXIS MOTOR TECHNOLOGY
Micro Step

SPINDLE SPEED
100.000RPM

SPINDLE POWER
0.75kW

NUMBER OF AXES
4 Axes

B AXIS TILT ANGLE
Endless

MAX TOOL SHAFT DIAMETER
3mm / 4mm

ATC CAPACITY
7

VOLTAGE / FREQUENCY
110v-230v / 50-60Hz

PRESSURIZED AIR REQUIREMENT (L/Min.)
- *

AIR PRESSURE (BAR)
- **

CAM SOFTWARE
Open System

DEVICE DIMENSIONS
306 x 470 x 615 mm

* In Case of Automatic Door: 15

** In Case of Automatic Door: 4

https://stomdevice.ru - стоматологическое и зуботехническое оборудование с доставкой по России и СНГ