stomdevice

REDON HYBRID
TECHNICAL DATASHEET



https://stomdevice.ru - стоматологическое и зуботехническое оборудование с доставкой по России и СНГ

Holder Types


Standart Holder


Premill Holder


Glass Ceramic Holder


Glass Ceramic / Premill Holder


Denture Holder

Applications


Abutments


Screw Retantion Bridge


Crown Bridge


Denture - Type 1


Denture - Type 2


Surgical Guide


Hybrid Abutment


Inlay, Onlay and Veners


Model Casting


Model


Splint


Telescope


Telescope Abutment

Material Types

Titanium	CoCr	Premill	Zirconia	Glass - Ceramic	Composite
PMMA	Alumina	Wax	Fiber	Peek	

Technical Specifications **Hybrid**

AXIS MOTOR TECHNOLOGY
Dijital AC Servo

SPINDLE SPEED
60.000RPM / STD

SPINDLE POWER
1.2kW / STD

NUMBER OF AXES
5 Axes

MAX. SLOPE ANGLE OF A AND B AXIS
±30 Degrees

MAX TOOL SHAFT DIAMETER
3 / 4 / 6mm

ATC CAPACITY
12

DRY AND WET MILLING
Yes

REFERENCING MILLING REQUIREMENT
No

VOLTAGE / FREQUENCY
110v - 230v / 50-60Hz

PRESSURIZED AIR REQUIREMENT (L/Min.)
100 L / Min.

AIR PRESSURE (BAR)
6

CAM SOFTWARE
Open System

DEVICE DIMENSIONS
560 x 630 x 650 mm

STANDARTS

Glass Ceramic / Premill Holder, Disc Holder, Zircon Bur Set, Allen Set, Spindle Cleaning Kit, Air Hose, Air Gun, Water Hose, Water Tank Cutting Oil, Cleaning Brush, Pump, Adapter, Ethernet Cable, Fuses, Usb

OPTIONS

Table, Vacuum Unit, Sinter Furnace, Scanner

redon the dental experience

https://stomdevice.ru - стоматологическое и зуботехническое оборудование с доставкой по России и СНГ